Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUTEC	
--------------------------------------	--

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

Model identifier: 5	5195401118M
---------------------	-------------

_	•			
Type	Λt	liont	COLIFC	Δ.
IVDC	VI.	HEIL	JUUIL	

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Welding		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter		Value	Parameter	Value	
	General product parameters:				
Energy consur mode (kWh/10 up to the neare	000 h), rounded	10	Energy efficiency class	Е	
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	1 050 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode pexpressed in W	oower (P _{on}),	9,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer	Height	15	Spectral power	See image	
dimensions	Width	70	distribution in the	in last page	
without	Depth	70		Dago 1 / 2	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivale	ent power ^(a)	Yes	If yes, equivalent power (W)	75
			Chromaticity	0,440
			coordinates (x and y)	0,403
Parameters for L	ED and OLED lig	ht sources:		
R9 colour render	ing index value	7	Survival factor	1,00
the lumen maintenance factor		0,96		
Parameters for LED and OLED mains light sources:				
displacement fac	tor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6
Claims that a source replaces light source with ballast of a partic	out integrated	_(b)	If yes then replacement claim (W)	-
Flicker metric (Ps	t LM)	1,0	Stroboscopic effect metric (SVM)	1,0

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

