Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark	k: LUTEC
-------------------------------	-----------------

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

Tyne	οf	liσht	sourc	۵.
IVDE	UI.	HEIIL	Souit	┖.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	welding		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

		1 Todact parar		
Parameter		Value	Parameter	Value
		General product p	arameters:	
<u> </u>	nption in on- 00 h), rounded st integer	10	Energy efficiency class	E
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	1 200 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pow pressed in W	ver (P _{on}), ex-	9,5	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	15	Spectral power dis-	See image
sions without	Width	70	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	70	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if					
any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,380		
		nates (x and y)	0,380		
Parameters for LED and OLED	light sources:				
R9 colour rendering index value	e 15	Survival factor	1,00		
the lumen maintenance factor	0,96				
Parameters for LED and OLED	Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent ligh source without integrated bal last of a particular wattage.	t	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0		

(a)'-': not applicable; (b)'-': not applicable;

