Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUTEC

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

Model identifier: 5287901012M

| _ | • | | | |
|------|-----|-------|--------------|-----|
| Type | ∩t. | liaht | COLLE | CO. |
| IVDE | UI. | HEIIL | 3 UUI | LC. |

| Lighting technology used: | LED | Non-directional or directional: | NDLS | | |
|-------------------------------|---------|---------------------------------|------|--|--|
| Light source cap-type | welding | | | | |
| (or other electric interface) | | | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No | | |
| Colour-tuneable light source: | No | Envelope: | - | | |
| High luminance light source: | No | | | | |
| Anti-glare shield: | No | Dimmable: | No | | |
| Duradicat negregations | | | | | |

Product parameters

| Froduct parameters | | | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--|--|
| Parameter | | Value | Parameter | Value | | |
| General product parameters: | | | | | | |
| <u> </u> | nption in on- 00 h), rounded st integer | 15 | Energy efficiency class | E | | |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 2 000 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 | | |
| On-mode power (P _{on}), expressed in W | | 14,8 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 | | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 | | |
| Outer dimen- | Height | 40 | Spectral power dis- | See image | | |
| sions without | Width | 35 | tribution in the | in last page | | |
| separate con- trol gear, light- ing control | Depth | 8 | range 250 nm to 800 nm, at full-load | | | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | |
|----------------------------------------------------------------------------|------|------------------------------|-------|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | |
| | | Chromaticity coordi- | 0,440 | | |
| | | nates (x and y) | 0,403 | | |
| Parameters for LED and OLED light sources: | | | | | |
| R9 colour rendering index value | 8 | Survival factor | 1,00 | | |
| the lumen maintenance factor | 0,96 | | | | |

(a)'-': not applicable; (b)'-': not applicable;

