Product Information Sheet

rounded to the second decimal

Height

Width

Depth

Outer

without

dimensions

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources			
Supplier's name or trade mark:	LUTEC		
Supplier's address: LUTEC EURO	PE NV, Herentalseb	aan 425, 2160 Wommel	gem, BE
Model identifier: 5288903118M	1		
Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Welding		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
	Product para	meters	
Parameter	Value	Parameter	Value
	General product p	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	18	Energy efficiency class	F
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 860 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), expressed in W	18,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and	-	Colour rendering index, rounded to	80

the nearest integer, or the range of CRIvalues that can be

distribution in the

power

Spectral

15

70

227

See image

in last page

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load			
Claim of equivaler	nt power ^(a)	Yes	If yes, equivalent power (W)	118		
			Chromaticity	0,380		
			coordinates (x and y)	0,380		
Parameters for LED and OLED light sources:						
R9 colour renderir	ng index value	14	Survival factor	1,00		
the lumen maintenance factor		0,96				
Parameters for LED and OLED mains light sources:						
displacement factor	or (cos φ1)	0,70	Colour consistency in McAdam ellipses	6		
Claims that an source replaces a light source withou ballast of a particular	a fluorescent out integrated	_(b)	If yes then replacement claim (W)	-		
Flicker metric (Pst	LM)	1,0	Stroboscopic effect metric (SVM)	1,0		

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

