Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trac	de mark: LUT	EC
-------------------------	--------------	----

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

Model ide	ntifier:	5288909118M
-----------	----------	-------------

_	•			
Type	Λt	liaht	COLIF	٠۵٠
IVDE	VI.	HEIIL	30ui i	. c.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Welding		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter		Value	Parameter	Value
		General product p	arameters:	
Energy consur mode (kWh/10 up to the neare	000 h), rounded	19	Energy efficiency class	Е
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	2 090 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500
On-mode pexpressed in W	oower (P _{on}),	19,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,50
for CLS, expres	idby power (P _{net}) ssed in W and second decimal	0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	15	Spectral power	See image
dimensions	Width	70	distribution in the	in last page
without	Depth	220		Dago 1 / 2

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity	0,463
		coordinates (x and y)	0,420
Parameters for LED and OLED lig	tht sources:		
R9 colour rendering index value	21	Survival factor	1,00
the lumen maintenance factor	0,96		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

