## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUTEC	
--------------------------------------	--

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

Model i	identifier:	560501	13118M
---------	-------------	--------	--------

Tν	pe	of	light	soui	ce:
. ,	P-	•			···

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	Welding			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Dradust parameters				

## **Product parameters**

Parameter		Value	Parameter	Value	
		General product p	arameters:		
	mption in on- 100 h), rounded st integer	9	Energy efficiency class	F	
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	750 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode pexpressed in W	oower (P <sub>on</sub> ),	8,3	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer	Height	15	Spectral power	See image	
dimensions	Width	32	distribution in the	in last page	
without	Depth	36			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	57	
		Chromaticity	0,380	
		coordinates (x and y)	0,380	
Parameters for LED and OLED lig	ht sources:	,		
R9 colour rendering index value	15	Survival factor	1,00	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0	

(a)'-': not applicable;

(b)<sub>'-'</sub> : not applicable;

