Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUTEC

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

Model identifier: 762222012M

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	Welding			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Product parameters				

General product parameters:	/alue
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer24Energy efficiency class	F
Useful luminous flux (douse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) Correlated colour nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), 23,5 Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (Pnet) - Colour rendering for CLS, expressed in W and index, rounded to rounded to the second decimal the nearest integer, or the range of CRI- values that can be set set	80
Outer Height 15 Spectral power	See image
dimensions Width 60 distribution in the	in last page
without Depth 76	
	Page 1 / 3

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	150		
		Chromaticity coordinates (x and y)	0,380 0,380		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	14	Survival factor	1,00		
the lumen maintenance factor	0,96				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0		

(a)'-' : not applicable;

(b)'_-' : not applicable;

