Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUT	EC
------------------------------------	----

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

Model identifier: 8304201	L448M
---------------------------	-------

Type	οf	lioht	SOLI	rce.
IVDE	UI.	ווצוונ	SUU	LE.

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	pin header			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	Yes	
Colour-tuneable light source:	Yes	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	Yes	
Product parameters				

Parameter		Value	Parameter	Value
		General product p	arameters:	
	mption in on- 100 h), rounded st integer	8	Energy efficiency class	F
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	670 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500
On-mode pexpressed in W	oower (P _{on}),	7,7	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,50
for CLS, expres	idby power (P _{net}) ssed in W and second decimal	0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	34	Spectral power	See image
dimensions	Width	44	distribution in the	in last page
without	Depth	48		Page 1 / 3

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity	0,463	
		coordinates (x and y)	0,420	
Parameters for LED and OLED lig	ght sources:			
R9 colour rendering index value	1	Survival factor	1,00	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

