Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUTEC
Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE
Model identifier: 8731201316

Type of light source:					
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	E27				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	Yes		
Colour-tuneable light source:	Yes	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		

Colour-tuneable light source: High luminance light source: No Anti-glare shield: Parameter Value Forduct parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux Sphere (360°) Ves Envelope: Parameter Yes Parameter Value Parameter Value F class Correlated colour 2700...6500 temperature,

up to the nearest integer			S. G.	
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	950 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500
On-mode prespressed in W	oower (P _{on}),	10,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,50
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	70	Spectral power	See image
dimensions	Width	41	distribution in the	in last page
without	Depth	41		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	70			
		Chromaticity	0,463			
		coordinates (x and y)	0,420			
Parameters for LED and OLED lig	tht sources:					
R9 colour rendering index value	4	Survival factor	1,00			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'_-' : not applicable;

(b)_{'-'} : not applicable;

